

## MATERIAL SAFETY DATA SHEET

## **YELLOW**

Version Number 1.0 Revision Date 09/18/2001 Page 1 of 5 Print Date 11/1/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW
Product code	:	CC10000496
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





LLOW	
sion Number 1.0 ision Date 09/18/2001	Page 2 Print Date 11/1/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

## MATERIAL SAFETY DATA SHEET



# VELLOW

			Print	Page 3 Date 11/1/
Storage		eep containers dry and tightly nd contamination. Keep in a c		e absorption
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.			required.
Eye/Face Protection	: Safety glasses with side-shields.			
Hand protection	: P:	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		safety practic
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide
	aj	ppropriate exhaust ventriation	at machinery.	
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type	ACGIH
Components	Value 10 mg/m3 5 mg/m3	Exposure time Time Weighted Average (TWA): PEL:	Exposure type Respirable fraction.	ACGIH OSHA Z
Components	Value 10 mg/m3 5 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL:	Exposure type	ACGIH OSHA ZI OSHA ZI
Components	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	Exposure type Respirable fraction.	ACGIH OSHA Z OSHA Z MX OEL
Components	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Respirable fraction. Total dust.	ACGIH OSHA ZI OSHA ZI MX OEL ACGIH
Components Calcium carbonate	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Exposure type Respirable fraction. Total dust. Total dust.	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z
Components Calcium carbonate	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Respirable fraction. Total dust.	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z
Components Calcium carbonate	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type Respirable fraction. Total dust. Total dust. as Ti	ACGIH OSHA ZI OSHA ZI MX OEL
Components Calcium carbonate	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Exposure type Respirable fraction. Total dust. Total dust. as Ti DPERTIES	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z MX OEL
Components Calcium carbonate Titanium dioxide	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 9. PHYSIC	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PR(	Exposure type Respirable fraction. Total dust. Total dust. as Ti DPERTIES ration rate : Not	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z
Components Calcium carbonate Titanium dioxide	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 <b>9. PHYSIC</b> : Solid : Pelle	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PR(	Exposure type Respirable fraction. Total dust. as Ti DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z MX OEL
Components Calcium carbonate Titanium dioxide Form Appearance Color Odor	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 <b>9. PHYSIC</b> : Solid : Pelle : YEL : Very	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): LOW Evapo ts Specifi LOW Bulk do	Exposure type         Respirable fraction.         Total dust.         as Ti         DPERTIES         ration rate       : Not         ric Gravity       : Not         lensity       : Not         pressure       : Not	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z MX OEL MX OEL
Components Calcium carbonate Titanium dioxide Form Appearance Color	Value 10 mg/m3 5 mg/m3 15 mg/m3 10 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 <b>9. PHYSIC</b> : Solid : Pelle : YEL : Very : Not c	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): LOW Evapo ts Specifi LOW Bulk do	Exposure type         Respirable fraction.         Total dust.         Total dust.         as Ti         DPERTIES         ration rate       : Not         ic Gravity       : Not         lensity       : Not         pressure       : Not         density       : Not	ACGIH OSHA Z OSHA Z MX OEL ACGIH OSHA Z MX OEL

## 10. STABILITY AND REACTIVITY

## MATERIAL SAFETY DATA SHEET



#### YELLOW Version Number 1.0 Page 4 of 5 Revision Date 09/18/2001 Print Date 11/1/2011 Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. products

**11. TOXICOLOGICAL INFORMATION** 

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



## MATERIAL SAFETY DATA SHEET

# YELLOW

sion Date 09/18/2001	Print Date 11/1/2
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous
TSCA Status	: All components of this product are listed on the TSCA inventory or ar exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65
Canadian Regulations:	
WHMIS Classification	: D2B
DSL	: Listed.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not Listed.
Japan ENCS	: Not Listed.
Korea KECI	: Listed.
Philippines PICCS	: Listed.
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.