

MATERIAL SAFETY DATA SHEET

PANTONE 394C

Version Number 1.0 Revision Date 09/07/2001 Page 1 of 5 Print Date 10/31/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PANTONE 394C
Product code	:	CC10000763
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PANTONE 394C

ision Date 09/07/2001	Page 2 Print Date 10/31/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Elementela L'inite	
Flammable Limits Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

PANTONE 394C

			Print D	Page 2 ate 10/31/
	aı	nd contamination. Keep in a c	łry, cool place.	
8. F	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protect	ive equipment normally r	required.
Eye/Face Protection	: Safety glasses with side-shields.			
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and		afety practic
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3 10 mg/m3	PEL: Time Weighted Average (TWA):	Total dust. as Ti	
	10 mg/m3	Time Weighted Average	as Ti	
Eorm	10 mg/m3 9. PHYSIC	Time Weighted Average (TWA): CAL AND CHEMICAL PRO	as Ti DPERTIES	OSHA Z MX OEL
Form Appearance	10 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): CAL AND CHEMICAL PRO	as Ti DPERTIES oration rate : Not	
Form Appearance Color	10 mg/m3 9. PHYSIC	Time Weighted Average (TWA): CAL AND CHEMICAL PRO the Evapo ets Specification of the terms of te	as Ti DPERTIES Dration rate : Not Tic Gravity : Not	MX OEI
Appearance	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very	Time Weighted Average (TWA): CAL AND CHEMICAL PRO E Evapo ets Specif E Bulk o faint Vapor	as Ti DPERTIES Oration rate : Not Tic Gravity : Not lensity : Not pressure : Not	MX OEI applicable. determined.
Appearance Color	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very	Time Weighted Average (TWA): CAL AND CHEMICAL PRO E Evapo ets Specif E Bulk o faint Vapor	as Ti DPERTIES Oration rate : Not Tic Gravity : Not lensity : Not pressure : Not	MX OEI applicable. determined. established
Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a	Time Weighted Average (TWA): CAL AND CHEMICAL PRO the Evapo ets Specif (E Bulk do traint Vapor determined. Vapor applicable pH	as Ti DPERTIES Tration rate : Not Tic Gravity : Not lensity : Not pressure : Not density : Not density : Not	applicable. determined. established applicable
Appearance Color Odor Melting point/range	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c	Time Weighted Average (TWA): CAL AND CHEMICAL PRO the Evapo ets Specif (E Bulk do traint Vapor determined. Vapor applicable pH	as Ti DPERTIES Tration rate : Not Tic Gravity : Not lensity : Not pressure : Not density : Not density : Not	MX OEI applicable. determined established applicable applicable
Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol	Time Weighted Average (TWA): CAL AND CHEMICAL PRO the Evapo ets Specif (E Bulk do traint Vapor determined. Vapor applicable pH	as Ti DPERTIES oration rate : Not fic Gravity : Not lensity : Not or pressure : Not or density : Not ic Not	MX OEI applicable. determined established applicable applicable
Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): CAL AND CHEMICAL PRO E Evapo ets Specif E Bulk o faint Vapor determined. Vapor applicable pH luble	as Ti DPERTIES oration rate : Not fic Gravity : Not lensity : Not or pressure : Not or density : Not ic Not	MX OEI applicable. determined established applicable applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): CAL AND CHEMICAL PRO E Evapo ets Specifi E Bulk of faint Vapor determined. Vapor applicable pH uble	as Ti DPERTIES oration rate : Not fic Gravity : Not lensity : Not or pressure : Not or density : Not ic Not	MX OEI applicable. determined established applicable applicable



MATERIAL SAFETY DATA SHEET

PANTONE 394C

sion Date 09/07/2001			Print Date 10/31/
Incompatible Materials	: Incompatible w	with strong acids and o	oxidizing agents.
Hazardous decomposition products			xide (CO), oxides of nitrogen ad smoke are all possible.
	11. TOXICOLOGI	CAL INFORMATIO	DN
health data for the individual			re effects listed are based on ex
<u>Toxicity Overview</u> This product contains the foll	lowing components whi	ich in their pure form	have the following characteristi
CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7 Titar	nium dioxide	Systemic effects	Respiratory system.
	12. ECOLOGICA	AL INFORMATION	[
Persistence and degradability	: Not readily bio	degradable.	
Environmental Toxicity	mental Toxicity : Chemicals are n of the polymer.		s they are bound within the matr
Bioaccumulation Potential	: Chemicals are n of the polymer.	•	s they are bound within the matr
Additional advice	: No data availab	ble.	
	13. DISPOSAL C	CONSIDERATIONS	
Product	recycling is pre waste material transportation a	eferred to disposal or i has the responsibility	t can be recycled. Where possib ncineration. The generator of for proper waste classification, ance with applicable federal, a.
Contaminated packaging	has the respons	ibility for proper was accordance with app	e. The generator of waste materi te classification, transportation licable federal, state/provincial
	14. TRANSPOR	T INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk	: Not regulated f	or transportation.	
ground) ICAO/IATA	: Not regulated f	or transportation.	



MATERIAL SAFETY DATA SHEET

PANTONE 394C

Version Number 1.0 Revision Date 09/07/2001 Page 5 of 5 Print Date 10/31/2011

	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not Listed.
Japan ENCS	:	Not Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.