830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 1 of 19 Print Date 04/26/2018

SAFETY DATA SHEET

830K-LT. CASHMERE/375

Section 1. Identification	n	
GHS product identifier	:	830K-LT. CASHMERE/375
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	CC10063655
Product type	:	solid
Relevant identified uses of the subst	tance	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word	:	No signal word.
		1/19

<u>PolyOne</u>

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 2 of 19 Print Date 04/26/2018

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

General	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

:

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10063655

CAS number/other identifiers

Ingredient name	%	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	25 - 50	9003-54-7
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	10 - 25	52829-07-9
Titanium dioxide	10 - 25	13463-67-7
Styrene	0 - 0.3	100-42-5
Carbon black	0 - 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018

Page 3 of 19 Print Date 04/26/2018

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	No specific data.
Ingestion	: No specific data.
Indication of immediate medical	tention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptom may be delayed. The exposed person may need to be kept under
Specific treatments	medical surveillance for 48 hours.No specific treatment.
	2/40

)ne

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 4 of 19 Print Date 04/26/2018

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Firefighting measures

:

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018

Page 5 of 19 Print Date 04/26/2018

Methods and materials for containment and cleaning up

Small spill	:	Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Styrene	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen
	minutes, unless otherwise stated. 425 mg/m3 100 ppm



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018

	OSHA PEL Z2 (1993-06-30)
	PEL: Permissible Exposure Level 100 ppm
	Ceiling-A concentration that should not be exceeded at any time
	during any part of the working day. 200 ppm
	Acceptable Maximum Peak (AMP) 600 ppm
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen
	minutes, unless otherwise stated. 425 mg/m3 100 ppm
	ACGIH TLV (1997-05-21)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 85 mg/m3 20 ppm
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level
	170 mg/m3 40 ppm
Carbon black	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 3.5 mg/m3
	1 0
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 3.5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 3.5 mg/m3
	Time Weighted Average (TWA)
	ACGIH TLV (2010-12-06)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
Decanedioic acid, bis(2,2,6,6-	
tetramethyl-4-piperidinyl) ester	
Titanium dioxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	NIOSH REL (1994-06-01)
	ACGIH TLV (1996-05-18)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 10 mg/m3
	remissione Exposure Level to inglind
2-Propenenitrile, polymer with	
Ethenylbenzene	
-	



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018		Page 7 of 19 Print Date 04/26/2018
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	solid [Pellets.]
Color	TAN

PolyOne

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018

Page 8 of 19 Print Date 04/26/2018

Odor	Faint odor.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive	: Lower: Not available.
(flammable) limits	Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: insoluble in water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	Not available.
SADT	Not available.
5.12 1	• - • • • • • • • • • • • • • • • • • •
Viscosity	: Dynamic: Not available.
	Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

PolyOne

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018

Page 9 of 19 Print Date 04/26/2018

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Styrene		· _			
	LD50 Oral	Rat	2,650 mg/kg	-	
	LC50 Inhalation	Rat	2,770 ppm	4 h	
	LC50 Inhalation	Rat	11.8 Mg/l	4 h	
Remarks - Dermal:	No applicable toxicity data				
Carbon black					
	LD50 Oral	Rat	15,400 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data			
Decanedioic acid, bis(2,2,6,6-t	etramethyl-4-piperic	linyl) ester			
Remarks - Oral:	No applicable toxic	No applicable toxicity data			
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				
Titanium dioxide					
Remarks - Oral:	No applicable toxic	city data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
2-Propenenitrile, polymer with	Ethenylbenzene				
	LD50 Oral	Rat	1,800 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data			
Conclusion/Summary	• Mixtu	re.Not fully tested.			

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 10 of 19 Print Date 04/26/2018

	Moderate				
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		Aixture.Not fully			
Eyes		/lixture.Not fully			
Respiratory	: N	/lixture.Not fully	v tested.		
Sensitization					
Conclusion/Summary					
Skin	: N	/lixture.Not fully	y tested.		
Respiratory	: N	/lixture.Not fully	y tested.		
Mutagenicity					
Conclusion/Summary	: N	/lixture.Not fully	y tested.		
Carcinogenicity					
Conclusion/Summary	: N	/lixture.Not fully	v tested.		
Classification					
	OSHA	IARC	NTP		
Product/ingredient	USIIA				
name	USIIA				
name Styrene		2B	Reasonably	anticipated to b	e a human carcinogen.
name Styrene Carbon black		2B 2B	Reasonably	anticipated to b	e a human carcinogen.
name Styrene Carbon black Titanium dioxide		2B 2B 2B 2B	Reasonably	anticipated to b	e a human carcinogen.
nameStyreneCarbon blackTitanium dioxide2-Propenenitrile, polymer		2B 2B	Reasonably	anticipated to b	e a human carcinogen.
name Styrene Carbon black Titanium dioxide		2B 2B 2B 2B	Reasonably	anticipated to b	e a human carcinogen.
nameStyreneCarbon blackTitanium dioxide2-Propenenitrile, polymer		2B 2B 2B 2B	Reasonably	anticipated to b	e a human carcinogen.
nameStyreneCarbon blackTitanium dioxide2-Propenenitrile, polymerwith Ethenylbenzene		2B 2B 2B 2B		anticipated to b	e a human carcinogen.
nameStyreneCarbon blackTitanium dioxide2-Propenenitrile, polymerwith EthenylbenzeneReproductive toxicity		2B 2B 2B 3		anticipated to b	e a human carcinogen.
name Styrene Carbon black Titanium dioxide 2-Propenenitrile, polymer with Ethenylbenzene Reproductive toxicity Conclusion/Summary	: N	2B 2B 2B 3	y tested.	anticipated to b	e a human carcinogen.
name Styrene Carbon black Titanium dioxide 2-Propenenitrile, polymer with Ethenylbenzene Reproductive toxicity Conclusion/Summary Teratogenicity	: N	2B 2B 2B 3 /lixture.Not fully /lixture.Not fully	y tested.	anticipated to b	e a human carcinogen.



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 11 of 19 Print Date 04/26/2018

Aspiration hazard Not available.		
Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical,	chemi	cal and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.
Delayed and immediate effects as	well as	chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 12 of 19 Print Date 04/26/2018

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Styrene	·		
	Acute LC50 4.02 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 0.0047 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute LC50 52 Mg/l Marine water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			•
	Acute EC50 1.4 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic	Acute		
plants:		1	1
	Acute EC50 0.72 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic	Acute		
plants:			-
	Acute NOEC 0.063 Mg/l Fresh	Aquatic plants - Algae	96 h
	water		
Remarks - Acute - Aquatic	Chronic		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Carbon black			
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
	12/19		



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 13 of 19 Print Date 04/26/2018

Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Decanedioic acid, bis(2,2,6,6-t	etramethyl-4-piperidinyl) ester		
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 8.6 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Titanium dioxide		1	
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		-
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
2-Propenenitrile, polymer with	Ethenylbenzene		
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic invertebrates.:	No applicable toxicity data		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:	FF		
830K-LT. CASHMERE/375	L		
Remarks - Acute - Aquatic	Chemicals are not readily available a	as they are bound within the	e polymer matrix.
invertebrates.:			
Conclusion/Summary		ly available as they are bou	nd within the
	polymer matrix.		



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 14 of 19 Print Date 04/26/2018

Persistence and degradability

Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.
Conclusion/Summary	:	Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Benzene, ethenyl-	0.35	13.49	low
Decanedioic acid, 1,10-bis(2,2,6,6-	0.35	-	low
tetramethyl-4-piperidinyl) ester			

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 15 of 19 Print Date 04/26/2018

Section 14. Transport information U.S.DOT 49CFR
Ground/Air/Water : Not regulated for transportation. International Air
ICAO/IATA : Not classified as dangerous goods under transport regulations. International Water
IMO/IMDG : Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations		ted States - TSCA 12(b) - Chemical export notification: None ne components are listed.
	Uni	ted States - TSCA 4(a) - Final Test Rules: Not listed
	Uni	ted States - TSCA 4(a) - ITC Priority list: Not listed
	Uni	ted States - TSCA 4(a) - Proposed test rules: Not listed
	Uni	ted States - TSCA 4(f) - Priority risk review: Not listed
	Uni	ted States - TSCA 5(a)2 - Final significant new use rules: Not
	liste	d
		ted States - TSCA 5(a)2 - Proposed significant new use rules: listed
	Uni	ted States - TSCA 5(e) - Substances consent order: Not listed
		ted States - TSCA 6 - Final risk management: Not listed
		ted States - TSCA 6 - Proposed risk management: Not listed
	Uni	ted States - TSCA 8(a) - Chemical risk rules: Not listed
		ted States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		ted States - TSCA 8(a) - Chemical Data Reporting (CDR): Not rmined
		ted States - TSCA 8(a) - Preliminary assessment report IR): Not listed
	Uni	ted States - TSCA 8(c) - Significant adverse reaction (SAR):
		listed
	Uni	ted States - TSCA 8(d) - Health and safety studies: Not listed
		ted States - EPA Clean water act (CWA) section 307 - Priority utants: Listed Acrylonitrile
	Ni	ckel antimony yellow rutile (C.I. Pigment Yellow 53)
		ted States - EPA Clean water act (CWA) section 311 -
		ardous substances: Listed
	Uni	ted States - EPA Clean air act (CAA) section 112 - Accidental

ne

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 16 of 19 Print Date 04/26/2018

release prevention - Flammable substances: Not listed **United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances:** Not listed **United States - Department of commerce - Precursor chemical:** Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential		Not listed
Chemicals)	•	Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Not applicable.

:

Composition/information on ingredients

Name	%	Classification
Styrene	0 - 0.3	F, AH, CH
Carbon black	0 - 0.3	СН
Decanedioic acid, bis(2,2,6,6- tetramethyl-4-piperidinyl) ester	10 - 25	АН
Titanium dioxide	10 - 25	СН
2-Propenenitrile, polymer with Ethenylbenzene	25 - 50	АН

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Styrene	100-42-5	0 - 0.3
-	C.I. Pigment Black 12	68187-02-0	3 - 5
	Nickel antimony yellow	8007-18-9	10 - 25



830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 17 of 19 Print Date 04/26/2018

	rutile (C.I. Pigment Yellow 53)		
Supplier notification	Styrene	100-42-5	0 - 0.3
	C.I. Pigment Black 12	68187-02-0	3 - 5
	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	10 - 25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	The following components are listed:
		Styrene
New Jersey	:	The following components are listed:
		Styrene
		Carbon black
		2-Propenenitrile, polymer with Ethenylbenzene
		Titanium dioxide
Dennerdronia		Nickel antimony yellow rutile (C.I. Pigment Yellow 53) The following components are listed:
Pennsylvania	:	Titanium dioxide
		i italiulii uloxide
		Nickel antimony yellow rutile (C.I. Pigment Yellow 53)
		C.I. Pigment Black 12
		Carbon black
		Styrene
<u>California Prop. 65</u>	1	
WARNING: This product contains a c	nemi	cal known to the State of California to cause cancer.
United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 18 of 19 Print Date 04/26/2018

Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

Date of printing	:	04/26/2018
Date of issue/Date of revision	:	04/09/2018
Date of previous issue	:	10/01/2012
Version	:	1.4
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)

830K-LT. CASHMERE/375

Version Number 1.4 Revision Date 04/09/2018 Page 19 of 19 Print Date 04/26/2018

References

UN = United Nations Not available.

•

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.